

PROJECT: _____


TYPE: _____ DATE: _____

NOTES: _____





FEATURES

With their smooth, flat and edgeless design, Oscar family recessed luminaires become a seamless part of ceiling decor. With 3 different light modules suited for ambient and accent lighting, the Oscar family is as highly functional as it is visually appealing. Numerous ordering options allow for further functional and artistic customization. Oscar recessed luminaires are available in larger sizes with higher lumen packages making them ideal for both residential and commercial settings.



Note: Trimless for drywall installation



SPECIFICATIONS


FIXTURE BODY	18 gauge powder coated steel body. Aluminum powder coated trim or trimless mesh plate
INSTALLATION TYPE	Remodel/existing ceiling N/C plate, IC Box on page 2
CUT HOLE	Trim: 3 1/4" x 3 1/4" Trimless: 3" x 3"
COLOR FINISH	Black/White/Custom
LIGHT MODULE	High output, high efficiency LED COB. Lumen Maintenance: 70%@50,000 hrs
INPUT VOLTAGE	120V - 277V
WATTAGE	10W IC Rated, 15W Non-IC Rated
POWER SUPPLY	ERP 10W or 15W, Constant Current 250mA or 350mA power supply Minimum operating temperature: -30° Enclosed in a Junction box with 12" flexible cable to mate to module connector
BEAM ANGLE	95°
CRI	90+
DIMMING	TRIAC/ELV/0-10V
LUMENS	10W, 380 Lumens & 15W, 580 Lumens, Dim to Warm: 15W, 360 Lumens
CCT OPTIONS	2700K/3000K/3500K/4000K, DIM (Dim to warm)
REFLECTORS	(W) Wide 95°
DIFFUSERS	(CL) Clear/(LN) Linear Spread/(HC) Honeycomb (FR) Frosted/(SP) Solite/(RE) Red Dichroic/(GR) Green Dichroic/(BL) Blue Dichroic/(OR) Orange Dichroic
APPROVAL	Damp
ELECTRICAL APPROVAL	Compliant
WARRANTY	

SPECIFICATION GUIDE


OSCAR	3	SHAPE	TRIM/TRIMLESS	FINISHES	LIGHT MODULE	BAFFLE FINISHES	WATTAGE	CCT	BEAM ANGLE	DIFFUSER	ADD-ONS									
OSC	3	S	SQUARE	T	TRIM	01	BLACK	WL	WALL WASH	01	MATTE BLACK	10	10W	27	W	95°	CL	CLEAR	DJ	DOUBLE JUNCTION BOX
				TL	TRIMLESS	02	WHITE			02	MATTE WHITE	15	15W	30			LN	LINEAR SPREAD		
														35			HC	HONEYCOMB		
														40			FR	FROSTED		
														DTW			SP	SOLITE		
									Dim To Warm								RE	RED DICHROIC		
									15W only								GR	GREEN DICHROIC		
																	BL	BLUE DICHROIC		
																	OR	ORANGE DICHROIC		

ORDERING GUIDE EXAMPLE:
Oscar / 3 / Square / Trim / White / Wall Wash / Chrome / 15W / 2700K / 95° Beam Angle / Clear Diffuser
CODE: OSC-3-S-T-02-WL-04-15-27-W-CL


REFLECTOR OPTIONS




BAFFLE FINISHES



DIFFUSER OPTIONS



ADD-ONS



NEW CONSTRUCTION PLATES + IC BOXES




NEW CONSTRUCTION PLATE

TRIM
30535-015

TRIMLESS
30536-012

CUT HOLE:
Trim: 3 1/4" x 3 1/4"
Trimless: 3" x 3"




TRIM
AT/IC Box: 30531-021
IC Box: 30531-017

CUT HOLE:
Trim: 3 1/4" x 3 1/4"
Trimless: 3" x 3"


TRIMLESS
AT/IC Box: 30532-023
IC Box: 30532-014

CUT HOLE:
Trim: 3 1/4" x 3 1/4"
Trimless: 3" x 3"





DRIVERS

- Compatible with TRIAC (forward-phase or leading-edge) ELV (reverse-phase or trailing edge) and 0-10V dimmers.
- ESSxxxW models: TRIAC and ELV dimming only at 120 Vac
- ESSxxxW models: ELV dimming only at 230 Vac
- 90° C maximum case hot spot temperature
- Class 2 power supply
- Lifetime: 50,000 hours at 70° case hot spot temperature (some models have a higher lifetime)
- IP64-rated (IP66 for ESST) case with silicone-based potting
- Protections: Output open load, over-current and short-circuit (hiccup), and over-temperature with auto recovery.
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class B (120 Vac) and Class A (277 Vac), and EN55015 (CISPR 15) at 220, 230, and 240 Vac.
- Complies with ENERGY STAR®, DLC (DesignLight Consortium®) and CA Title 24 technical requirements
- Worldwide safety approvals



OSCAR
OSCAR SMALL APERTURE SQUARE WALL WASH
PHOTOMETRICS



15W 1-LIGHT WALL WASH CLEAR