

PROJECT: \_\_\_\_\_


TYPE: \_\_\_\_\_ DATE: \_\_\_\_\_

NOTES: \_\_\_\_\_



## FEATURES

Tango is a specification grade LED recessed family, offering multiple options for design and functionality. Round and square, trim and trimless, 1, 2 and 3 light options and several task specific trim designs. Tango features 90+ CRI high performance LED chips, drivers with multi dimming capabilities and industry leading ease of installation and services.



**STANDARD DRIVER BOX:** MINIMUM HEIGHT CLEARANCE: 9.5"

**MAX CEILING THICKNESS:** TRIM 1.25" TRIMLESS 1.5"

## SPECIFICATIONS

<b>FIXTURE BODY</b>	18 gauge powder coated steel body. Aluminum powder coated trim or trimless mesh plate
<b>INSTALLATION TYPE</b>	Remodel/existing ceiling N/C plate on page 2
<b>CUT HOLE</b>	Trim: 10 1/8" x 3 3/8" Trimless: 10 1/2" x 3 1/4"
<b>COLOR FINISH</b>	Black/White/Custom
<b>LIGHT MODULE</b>	High output, high efficiency LED COB. Lumen Maintenance: 70%@50,000 hrs
<b>INPUT VOLTAGE</b>	120V - 277V
<b>WATTAGE</b>	45W IC Rated
<b>POWER SUPPLY</b>	3 x ERP 15W, Constant Current 350mA power supplies Minimum operating temperature: -30° Enclosed in a Junction box with 12" flexible cable to mate to module connectors
<b>CRI</b>	90+
<b>DIMMING</b>	TRIAC/ELV/0-10V
<b>LUMENS</b>	3 x 15W, 2490 Lumens
<b>CCT OPTIONS</b>	3000K/4000K
<b>REFLECTORS</b>	(N) Narrow 15°
<b>DIFFUSERS</b>	(CL) Clear
<b>APPROVAL</b>	Damp
<b>ELECTRICAL APPROVAL</b>	Compliant
<b>WARRANTY</b>	

## SPECIFICATION GUIDE

TANGO	3-LIGHT	TRIM/ TRIMLESS		FINISH		LIGHT MODULE x 3		WATTAGE		CCT
TGO	3	T	TRIM	01	BLACK	SUSUSU	SUSPENSION	15	15W	30
		TL	TRIMLESS	02	WHITE					40

### ORDERING GUIDE EXAMPLE:

Tango / 3-Light / Trim / White / Suspension / Suspension / Suspension  
15W / 3000K

CODE: **TGO-3-T-02-SUSUSU-15-30**

For custom module configuration, email [sales@eurofase.com](mailto:sales@eurofase.com)

#### NEW CONSTRUCTION PLATES



#### NEW CONSTRUCTION PLATE TRIM


41952-016

**TRIMLESS**  
43668-014

#### CUT HOLE:


Trim: 10 1/8" x 3 3/8"

Trimless: 10 1/2" x 3 1/4"



#### DRIVERS

- Compatible with TRIAC (forward-phase or leading-edge) ELV (reverse-phase or trailing edge) and 0-10V dimmers.
- ESSxxxW models: TRIAC and ELV dimming only at 120 Vac
- ESSxxxW models: ELV dimming only at 230 Vac
- 90° C maximum case hot spot temperature
- Class 2 power supply
- Lifetime: 50,000 hours at 70° case hot spot temperature (some models have a higher lifetime)
- IP64-rated (IP66 for ESST) case with silicone-based potting
- Protections: Output open load, over-current and short-circuit (hiccup), and over-temperature with auto recovery.
- Conducted and radiated EMI: Compliant with FCC CFR Title 47 Part 15 Class B (120 Vac) and Class A (277 Vac), and EN55015 (CISPR 15) at 220, 230, and 240 Vac.
- Complies with ENERGY STAR®, DLC (DesignLight Consortium®) and CA Title 24 technical requirements
- Worldwide safety approvals



#### PHOTOMETRICS

